

SuperLead

苏州斯普锐智能系统有限公司

7200HP

立式二维码扫描小平台 (百万像素)
Presentation Scanner (Megapixels)



大视野

Large Field of View

高端、大气
High-performance



- 物体自感应
- 内置RS232和USB接口
- Object self induction
- Build in RS232 and USB interface
- 超大扫描窗口
- 3种工作模式 (普通模式, 手机屏模式, 以及快速移动模式)
- Super large reading window
- 3 working modes (normal mode, mobile phone screen mode and fast moving mode)

Physical Characteristics	
尺寸Dimensions:	105mm x 146mm x 70mm
重量Weight:	418g
电压Voltage:	5 VDC
电流Current:	500mA (Operating)
Performance Characteristics	
光源Light Source:	Illumination: 650nm RED LED
视场角Field of View:	50° (H) x 35° (V)
偏转/倾斜/旋转Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度Print Contrast:	25% minimum reflective difference
运动容差Motion Tolerances	up to 600 cm per second
接口支持Interfaces Supported:	USB, RS232
Symbology Decode Capability	
一维条码1-D:	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, China Postal, Korean Postal, etc.
二维条码2-D:	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.
条码精度Minimum Resolution	4 mil Code39
User Environment	
工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	0% to 95% relative humidity, non-condensing
抗震动Shock Specifications:	Designed to withstand 1.5m(5') drops
环境光免疫Ambient Light Immunity:	100.000 Lux.
Decode Ranges	
5 mil (Code 39)	0mm-60mm
13 mil (100%Upca)	0mm-200mm
Performance may be impacted by bar code quality and environmental conditions	
   	